



OUTFEED CONVEYOR

M108S TRIMMER COMPATIBLE

INCREASED QUALITY CONTROL AND PRODUCT CONSISTENCY

Create a continuous quality control system utilizing the Outfeed Conveyor attached to the M108S Trimmer. By positioning the conveyor and quality control staff on the outfeed of the trimmer, the trimmed flowers can be inspected immediately, reducing errors, lowering costs, and streamlining your harvesting process.

With a standard quality control process using the Outfeed Conveyor, you can deliver consistent, high-quality flower every harvest. The stainless steel construction and 60-second disassembly maintain the efficiency introduced by the M108S Trimmer.

KEY FEATURES

Stainless steel construction

Engineered specifically for cannabis processing

Washdown-rated components

Tool-free 60-second disassembly

Easily pairs with the Mobius M108S Trimmer or Mobius Autofeed Conveyor

Adjustable height to fit your Mobius trimming workflow

Variable speed and direction controls

GMP ready

SPECIFICATIONS

OUTFEED CONVEYOR

Construction	304 Stainless Steel
Belt Material	Fully-Encased Anti-Microbial Polyurethane
Tool-Less Disassembly	Yes
Motor	1 / 10 HP
Speed Range	6 – 35 ft / min
Belt Dimensions	16" (41 cm) W 72" (183 cm) L
Overall Dimensions	27" (69 cm) W 72" (183 cm) L 31" (79 cm) H
Weight	120 lbs (54 kg)
Power Requirements	NA: 120 V, 1.5 A ITL: 240 V, 0.75 A
Recommended PPE	Ear Protection Eye Protection Dust Mask
Warranty	1 Year or 1,000 Hours
Motor Markings	UL, CSA, CCC, EN, CE

