# MM20 & MM65 HASH WASHERS

## INDUSTRIAL-SCALE HASH WASHERS



Achieve optimal trichome separation and high yields of bubble hash. The Mobius MM20 and MM65 ensure maximum potency for solventless extraction.

#### **AUTOMATIC WASHING CYCLES**

Choose the settings for your wash sequence and start the machine. The washer will automatically run through the cycle with your pre-set spin directions and timer.

#### **CUSTOMIZED SYSTEM**

The MM hash washer series is available as an all-inclusive washing and collection kit, or as modular components. Get the complete system ready to operate, or select individual components to upgrade or outfit an existing bubble hash workflow.

#### REDUCE LABOR AND BOOST EFFICIENCY

All-in-one system and automatic operation free up personnel for other tasks. Prep hash bags, cold trays, and collection utensils while the flower is washing.

#### **EASY CLEANING**

Reduce downtime with the built-in tilt system for quick and easy cleaning. FDA-approved food-safe stainless steel construction ready for any GMP-certified facility.

#### **GENTLE ON TRICHOMES**

No-shear impeller creates a gentle vortex for easy trichome separation. Built-in pump and drain let you cycle the water back through the washer for additional rounds of extraction.

#### KEY FEATURES

Built-in thermometer

Savable settings

Customizable solutions

Stainless steel construction

Touch-screen HMI

Easy collection bag setup

Built-in step stool



#### SPECIFICATIONS

### MM20 & MM65 HASH WASHERS

Capacity       20 Gal       65 Gal         Overall Dimensions       36" (91 cm) L       45" (114 cm) L         33" (84 cm) W       41" (104 cm) W         64" (163 cm) H       75" (191 cm) H         Weight       440 Lbs       645 Lbs
Overall Dimensions       33" (84 cm) W       41" (104 cm) W         64" (163 cm) H       75" (191 cm) H
Weight 4401hs 6451hs
- THO EDS 043 EDS
Bag Size Compatibility 5 Gal 10 - 20 Gal
Impellar Speed 1-11 1-11
Recipe Banks 10 10
Vessel 304 Stainless 304 Stainless
Impeller Material  NSF/USDA-certified  Delrin  NSF/USDA-certified  Delrin
Motor Power 1/4HP 1/2HP
Power Req. 120 V, 10 A 120 V, 10 A

